



# PT. ADITA FABRICATION, REPAIR & SUPPLIER

Jl. Sosial Dalam - Lamaru Balikpapan  
Telp (0542) 790909, Fax (0542) 790909  
Email : ptadita@gmail.com

## PT. ADITA'S FACILITY, EQUIPMENTS, & MACHINERIES

Front Yard (61 M x 23 M)



Meeting Room & Lobby 1st Floor, & Office 2nd Floor



Fabrication Yard (30 M x 6 M)



Warehouse, Tool Room & Consumables Store



Back Yard (61 M x 23 M)



Maintenance Area



Genset Hartech



## Horizontal Lathe Machine (3 Meters) CW 6280B



Specification	CW 6280B/3000
Distance Between Center	3000 mm
Swing over Carriage	480 mm
Swing over Bed	800 mm
Max. cross travel of lower slide	500 mm
Max. travel of top slide	200 mm
Max. travel of tailstock quill	250 mm
Swing over Gap	1000/310mm
Spindle Bore	104 mm
Spindle Speeds	18 speeds 5.4-720 r/min
Width of Bed	600/RC52
Main motor power	11 or 15 kW
Net Weight	5500 kg

### Standard Accessories

- 3 – jaw chuck Ø 315
- 4 – jaw chuck Ø 500
- Face plate Ø 800
- Steady rest Ø 40 – Ø 320
- Follow rest Ø 30 - Ø 130
- Center and sleeve metric
- Lillumination, cooling

**Horizontal Lathe 2M - San Shing Taiwan**  
**Mesin Bubut Kodok**



<b>Specification</b>	<b>San Shing 2 M</b>
Distance Between Center	2000 mm
Swing over Carriage	1000 mm
Swing over Bed	1500 mm
Spindle	4 Inchi +

## Horizontal Lathe Machine (0,75 Meters) CQ 6230 A

Specification	CQ 6230 A
Swing Over Bed	330 MM
Swing Over Gap	430 MM
Swing Over Carriage	178 MM
Distance Between	914 MM
Spindel Bore	38 MM
Headstock Taper	MT5
Spindle Speeds	60 - 1500 Rpm
Threads of Leadscrew	8 tpi
Threads Imperial Pitches	60 - 4 tpi
Threads Metric Pitches	0.4 - 7 MM
Cross Feed Range	0.014 - 0.3448 MM/R
Longitudinal Feed Range	0.00527 - 12912 MM/R
Top Slide Cover	95 MM
Cross Slide Travel	175 MM
Saddle Travel	800 MM
Tailstock Travel	100 MM
Tailstock Taper	MT3
Motor Power	1.5 HP
Net Weight	360 KG
Dimension	1676 735 x 1168 MM



## Horizontal Lathe Run Master 1 M



Specification	Run Master 1 M
Distance Between Center	1000 mm
Swing over Carriage	460 mm
Swing over Bed	1500 mm
Spindle	2 Inchi
Width of Bed	600 MM
Machine Weight	5000 KG

## Horizontal Lathe 2 Meters - Magnum Cut FEL-2080GNX



Specification	Magnum Cut FEL-2080GNX
Admissible Diameter on the Bar	500 mm
Admissible Diameter on the Cross Carriage	350 mm
Allowable Diameter in the Armhole	750 mm
Distance between Center	2000 MM
Cross Car Course	270 MM
Bus Width	335
Passage Diameter	80
Number of Speeds	12
Speed Range	35-1650 Rpm
Sleeve Diameter	75 MM
Taper	MT 4
Metric Thread	0,5 - 20
Thread per Inch	15/8" - 72TPI
Main Engine	7,5/10,0 KW
Coolant Pump Motor	1/6 HP
Equipment Voltage	220 V
Net weight	2800 KG
Length	3520 MM
Width	1150 MM

## Horizontal Lathe 6 M CQ 62110F (Double Sadle)



Specification	CQ 62110F
Distance Between Center	6000 mm
Swing over Carriage	1800 mm
Swing over Bed	2200 mm
Max. cross travel of lower slide	790 mm
Max. travel of tailstock quill	250 mm
Spindle Bore	105 mm
Spindle Speeds	18 speeds, 4-530r/min
Width of Bed	600/RC52
Main motor power	11 or 15 kW
Net Weight	9000 kg

## Shaping Machine B0635



Specification	B0635
Panjang Langkah	350 MM
Derajat Putar	90 Derajat
Berat	1100 KG
Dinamo	1,5 KW, 1450 RPM
Power	380 V

## Radial Drill THZ3063x20A



Specification	THZ3063x20A
Max.drilling diameter	63 MM
Distance from spindle nose to table surface	290-1540 MM
Distance between spindle axis and column surface	430-1930 MM
Spindle travel	400 MM
Spindle taper	MT5
Spindle speeds range	16-1250 Rpm
Spindle speed steps	16
Spindle feeding range	0.04-3.20 MM/r
Spindle feeding steps	16
Rocker rotary angle	±360°
Main motor power	5.5 KW
Lifting motor power	0,75 KW
Machine Weight	6500 KG
Machine Overall dimensions	3000x1250x3300 MM

### Milling Nantong X6325



Model NO.	X6325	Milling Cutter Type	Vertical Milling Cutter
Milling Cutter Structure	Indexable Type	Controlling Mode	Artificial
Automatic Grade	Semiautomatic	Precision	High Precision
Certification	CE	Condition	New
Machine	Turret Milling Machine	Spindle Motor	2.0 /2.4 Kw
Taper	R8	Diameter of Spindle Hole	15mm
Table Size	1270X250 Mmm	Spindle Axis Travel	130mm
Spindle Power Feed Range	0.047 0.09 0.148 mm/R	Loading Weight	200kg
Spindle Speed	65-4760 Rpm	Feeding Driving Motor	0.25kw 1400 R/Min
Coolant Pump	0.04 Kw	Table Power Feed	18-326 R/Min
T-Slot	3X14mm	Table Travel	820X360X400mm
Adjust Slotting Head	3-100mm	Transport Package	1760X1690X2160mm
Specification	1300kgs	Trademark	nantong

**WELDING MACHINES PT. ADITA**

**Miller Big Blue Air 600 A**



**3 Unit Redbo MMA 500**



**MIG MAG Kobe Weld Xi 500 & Megatech 500**



**2 Unit iller SRH 500**



## Lifting Equipment & Transportation

OHC 5 Tons (Abuse)



Forklift 2,5 Ton



Mitsubishi Colt Diesel HD 125PS Dump Truck 2006



Izuzu Panther Pick Up 2015



LINE BORING MACHINES

